

BEST AVAILABLE COPY

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings of claims in the applications:

1. (Currently Amended) An accessory for a line trimmer that includes a main pole with a trimmer head attached at one end, said accessory comprising:

- a. an extension arm having a distal end and a proximal end;
- b. a wheel assembly attached to said distal end of said extension arm, said wheel assembly including at least one wheel rotatably mounted thereon; and,
- c. a first clamp member used to longitudinally align and attach said extension arm to a main pole of a line trimmer so that said distal end extends forward from the trimmer head, said first clamp member able to be attached at different positions to the main pole thereby allowing the distance between the trimmer head and said wheel assembly to be adjusted thereby allowing the trimmer head to be positioned at different heights for cutting vegetation at a constant height when the wheel assembly is rolled over a support surface the enabling the length of said extension arm to be axially rotated over the main pole and adjusted in length for supporting the line trimmer at different elevations when said wheel is moved over a support surface, said first clamp member also enabling said extension arm to pivot over an axis perpendicular to main pole.

2. (Currently Amended) The accessory, as recited in Claim 1, further including said wheel assembly being rotatably attached to said distal end of said extension arm and a locking means enabling said wheel assembly to be for selectively locked locking said wheel assembly in a desired position on said extension arm.

1 3. (Currently Amended) The accessory, as recited in Claim 1, further including a second
2 clamp member attached to said extension arm that enables the length of said extension pole
3 ~~relative to~~ between said main pole first clamp member and said wheel assembly to be
4 adjusted thereby allowing and allows the pitch of said extension arm relative to ~~said the~~ main
5 pole to be adjusted.

6
7 4. (Currently Amended) The accessory, as recited in Claim 3, further including said wheel
8 assembly being rotatably attached to said distal end of said extension arm and a locking
9 ~~means enabling said wheel assembly to be~~ for selectively locked locking said wheel assembly
10 in a desired position on said extension arm.

11
12 5. (Original) The accessory, as recited in Claim 3, wherein said first and second clamp
13 members are formed on a rotating L-shaped bracket selectively attaching said extension arm
14 to the main pole, said L-shaped bracket includes a first support flange that supports said first
15 clamp member and a second support flange that supports said second clamp member, said
16 first support flange and said second support flange being perpendicularly aligned thereby
17 perpendicularly aligning said first clamp member and said second clamp member

18
19 6. (Currently Amended) The accessory, as recited in Claim 4 5, further including said wheel
20 assembly being rotatably attached to said distal end of said extension arm and a locking means
21 enabling said wheel assembly to be selectively locked in a desired position on said extension
22 arm. ~~wherein said first and second clamp members are formed on a rotating L-shaped bracket~~
23 ~~selectively attaching said extension arm to the main pole, said L-shaped bracket includes a~~

1 ~~first support flange that supports said first clamp member and a second support flange that~~
2 ~~supports said second clamp member, said first support flange and said second support flange~~
3 ~~being perpendicularly aligned thereby perpendicularly aligning said first clamp member and~~
4 ~~said second clamp member.~~

5

6 7. (Original) The accessory, as recited in Claim 1, wherein said first clamp member includes
7 an upper clamp member, a lower clamp member, a center post, a pivoting handle attached to
8 said post, and a strap, said upper and lower clamp members including teeth that selectively
9 engage when said upper and lower clamp members are forced together, said strap member
10 extending through said lower clamp member and wrapped around a main pole on a line
11 trimmer, said center post extending through said upper clamp member and connecting to said
12 strap to connect said upper clamp member and said lower clamp member together and to
13 tighten said strap around the main pole.

14

15 8. (Currently Amended) An accessory for a line trimmer that includes a main pole with a
16 trimmer head attached at one end, said accessory comprising:

- 17 a. an extension arm having a distal end and a proximal end;
- 18 b. a wheel assembly attached to said distal end of said extension arm, said wheel
19 assembly including at least one wheel mounted thereon;
- 20 c. a first clamp member used to longitudinally align and attach said extension
21 arm to a main pole of a line trimmer, said first clamp member enabling the length of said
22 extension arm between the that extends from a trimmer head and said wheel assembly to be
23 adjusted for supporting a trimmer head at different elevations when the line trimmer is

1 ~~positioned with said wheel on said~~ is rolled across a support surface, to move said trimmer
2 ~~head at a constant elevation over a support surface, said first claim member also enabling said~~
3 ~~extension arm to pivot over an axis perpendicular to said main pole;~~

4 d. a second clamp member attached to said extension arm that enables the
5 angular orientation of said extension arm to be adjusted relative to the main pole on a line
6 trimmer; and,

7 e. a locking member attached to said wheel assembly enabling said wheel
8 assembly to be selectively locked in position on said extension arm.

9
10 9. (Original) The accessory, as recited in Claim 8, wherein said first and second clamp
11 members are formed on a rotating L-shaped bracket selectively attaching said extension arm
12 to the main pole, said L-shaped bracket includes a first support flange that supports said first
13 clamp member and a second support flange that supports said second clamp member, said
14 first support flange and said second support flange being perpendicularly aligned.

15
16 10. (Original) The accessory, as recited in Claim 8, wherein said first clamp member includes
17 an upper clamp member, a lower clamp member, a center post, a pivoting handle attached to
18 said post, and a strap, said upper and lower clamp members including teeth that selectively
19 engage when said upper and lower clamp members are forced together, said strap member
20 extending through said lower clamp member and wrapped around a main pole on a line
21 trimmer, said center post extending through said upper clamp member and connecting to said
22 strap to connect said upper clamp member and said lower clamp member together and to
23 tighten said strap around the main pole.

1 11. (Original) The accessory, as recited in Claim 9, wherein said first clamp member
2 includes an upper clamp member, a lower clamp member, a center post, a pivoting handle
3 attached to said post, and a strap, said upper and lower clamp members including teeth that
4 selectively engage when said upper and lower clamp members are forced together, said strap
5 member extending through said lower clamp member and wrapped around a main pole on a
6 line trimmer, said center post extending through said upper clamp member and connecting to
7 said strap to connect said upper clamp member and said lower clamp member together and to
8 tighten said strap around the main pole.

9
10 12. (Original) The accessory, as recited in Claim 8, wherein said wheel is rotatably mounted
11 on said wheel assembly.

12
13 13. (Original) The accessory, as recited in Claim 8, wherein said wheel assembly is fixed in
14 position on said extension pole.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.